

A Review on Adsorptive and Photocatalytic Removal of Pharmaceuticals from Aqueous Solution onto Cost Effective Nano Adsorbents

SWATI GOYAL

Department of Chemistry, Dr. A. P. J. Abdul Kalam University, Indore

Corresponding Author Email: swatipc2011@gmail.com

Abstract—A number of research activities have been carried out by many researchers to explore most suitable and efficient technique for the removal of pharmaceuticals from industrial effluent. Various techniques namely coagulation, precipitation, filtration, reverse osmosis, ion exchange, adsorption and photocatalytic degradation have been used to remove organic and inorganic compounds from the aquatic environment. Among all the reported methods, the adsorption study has been found a most promising technique for the removal of these types of contaminants. A phenomena of accumulation of substances on the surface of solid by some physical or chemical process than into the bulk is known as adsorption. Over the last decades, adsorption has gained importance as a purification and separation technique on an industrial scale and become an attractive option for industrial water treatment. This review paper would be supportive to find the most capable technique for the removal of dye contaminants from industrial effluent taking into consideration the merits and demerits of each method.

Index Terms—Water pollution, Pharmaceuticals, Removal techniques, Adsorption, Adsorbents.

I. INTRODUCTION

Water is an essential constituent of all animal and vegetable matter and forms about 75% of the matter of earth's crust. Water is used for many purposes including industrial and municipal purposes. Each industry has its own water requirements and sometimes adequate supply of water may be very suitable for one industry but the same may be dangerous for the other. It is, therefore, extremely important to take into account the uses of water for the work to be carried out, its suitability based on the results of chemical analysis and bacteriological examinations. The quality and quantity of available water are important in the location of a chemical plant. For this purpose surface water as well as ground water may be used, but the supply must be adequate and continuous throughout the year. More than 50% of water supply used in chemical plants is utilized for cooling purpose. Water can be obtained from different sources therefore it has a large number of impurities. For example, water gets impurities from ground or soil with which it comes into contact. Water also gets contaminated with sewage and industrial wastes or effluents when these are allowed to flow into running water or through percolation through the ground. In all over India, an estimated 90% of waste-water is discharged directly into

rivers and streams without treatment. The main cause of wastewater production is the manufacturing or chemical processes in industries. Industrial waste-water generally contains specific and readily identifiable chemical compounds. But water pollution is concentrated within a few sub sectors, mainly in the form of toxic wastes and organic pollutants. Out of this, a large portion can be traced to the processing of industrial chemicals and to the food product industries. The textile industry, a major consumer of water for several of its wet processing operations, is also a major producer of effluent waste-water containing organic surfactants, salts, acids, alkalis, solvents and pharmaceuticals as some of its main constituents. Pharmaceuticals, though present in only small amounts are highly detectable and thereby are capable of causing serious problems of an aesthetic nature in the receiving water bodies. Major sources of water pollution are showed in figure 1.



Figure 1: Water pollution due to pharmaceuticals.

India's dye industries produce every type of pharmaceuticals and pigments. India is the second largest exporter of pharmaceutical stuffs and intermediates developing countries, after China. About 90,000 tones of pharmaceutical stuff and pigments produced frequently in India. Mostly the textile industries have largest consumption of pharmaceutical stuffs, at nearly 80%. Wastewater generated from textile industries pose a threat to the environment because a large amount of chemical containing pharmaceuticals are used for various industrial applications and a some amount of these wastes enter the environment via wastewater. The presence of even very low concentrations of pharmaceuticals in effluent is

highly visible and degradation products of these textile pharmaceuticals are often carcinogenic [1]. Dye removal has ecological and economical importance. The interaction between polymer and dye leads to the formation of polymer-dye complex which exhibits many interesting and important practical features. Coulombic, hydrophobic and steric interactions are major factors governing the thermo chemical and dynamic aspects of complex formation. The interactions of the hydrogels with pharmaceuticals are of principal interest. Taking into account the environmental requirements, the development of water-based coloured polymer materials is one of the modern targets for the chemical industry. The textile finishing industry has a specific water demand of about 100-500 L.Kg⁻¹ product [2,3]. Colour in textile effluents has become particularly identified with the dyeing of cotton products and the use of reactive pharmaceuticals. Upto 30% of the used pharmaceutical stuffs remain in the spent dye-bath after the dyeing process [4]. Out of many contaminants present in wastewater, such as acids, bases, toxic organic and inorganic dissolved solids and colours, colours are considered as the most undesirable and are mainly caused by pharmaceuticals [5]. Pharmaceutical are synthetic aromatic water soluble dispersible organic colourants, having potential applications in various industries. The pharmaceutical stuff usage has been increased day by day because of tremendous increase of industrialization and man's urge for colour [6]. Pharmaceutical pictorial value is high, less than 1 ppm of the dye produces obvious colouration [7]. Synthetic pharmaceutical stuffs are used extensively in textile, paper, printing industries and dye houses. The effluents of these industries are extremely coloured and the discarding of these wastes into water bodies causes damage to the environment. Removal of colour from dye bearing wastewater is a complex problem because of difficulty in treating such wastewaters by conventional treatment method [8]. Dye industries and many other industries which used pharmaceuticals and pigments generated wastewater, characteristically high in colour and organic content. Presently, it was estimated about large number of different commercial pharmaceuticals and pigments exists and over huge tones are produced annually worldwide [9]. About 10-15% of the total pharmaceuticals from various textile and other industries get discharged in water causing extensive pollution [10,11]. From an environmental point of view, the removal of synthetic pharmaceuticals is of great concern, since some pharmaceuticals and their degradation products may be carcinogens and toxic [12]. Dye pollutants from textile dye industries are an important source of environment contamination [13]. It is estimated that some of the pharmaceuticals are lost during processes and is released in wastewater. The release of this colored wastewater poses a major problem for the industry as well as a threat to the environment [14]. The treatment of highly coloured waste-water containing hazardous industrial chemical effluents is one of the growing needs of the present time [15, 16]. Colour in water body is not only aesthetically unpleasant but also interferes light penetration and reduces photosynthetic action. Many pharmaceuticals or their metabolites have toxic as well as carcinogenic, mutagenic and

teratogenic effects on aquatic life and humans [17, 18]. Many industries use pharmaceuticals extensively in different operations such as textile, paper, plastic, leather tanning etc [19, 20]. All pharmaceuticals used in textile industry are designed to resist fading upon exposure to sweat, light, water, many chemicals including oxidizing agents and microbial attack. During processing up to 15% of the used pharmaceutical stuffs are lost in industrial effluents [21, 22]. Major classes of pharmaceuticals used are azo, anthraquinone and triphenylmethane. In addition to their visual effect and adverse impact in terms of Chemical Oxygen Demand (COD), many synthetic pharmaceuticals show their toxic, carcinogenic and genotoxic effects [23]

II. RELIABLE METHODS OF PHARMACEUTICALS REMOVAL

Data During the last 35 years India has become a major producer of pharmaceuticals and pigments. A number of pharmaceuticals are prepared to fulfill the needs of not only the textile industries but also of other industries like paper, rubber, plastics, paints, printing inks, art and craft, leather, food, drug and cosmetics [24]. In particular, printing and dyeing unit wastewaters contain several types of coloring agents, which are difficult to be treated by biological methods [25]. Pharmaceutical even in very low concentrations, can affect the aquatic life and the food web. Some pharmaceuticals are carcinogenic and mutagenic in nature therefore some techniques are required to remove the pharmaceuticals from wastewater. The treatment of highly coloured wastewater containing hazardous industrial chemical effluents is one of the growing needs of the present time [26][27]. Various chemical and physical methods like coagulation, flocculation, adsorption, photocatalytic oxidation, chemical oxidation and froth flotation processes have been used by a number of research workers for the removal of organics as well as inorganic from wastewaters. [28]. Recently, sophisticated instrumentation involving electrochemical, photochemical, chromatographic techniques, etc., has also been employed for this purpose [29,30]. Several scientists have also tried water treatment of pharmaceuticals over low cost materials using the adsorption technique. Photo catalytic degradation is considered a favoured, promising, cleaner, and greener technology for the removal of toxic organic and inorganic pollutants from water and wastewater [31]. Our laboratories are also contributing in this direction with adsorption and electrochemical methods for the removal of some toxic textile and food pharmaceuticals [32-34]. Many industries like the textile industry used pharmaceuticals to colour their products and thus produce wastewater containing organics with a strong color, where in the dyeing processes the percentage of dye lost wastewater is 50% of the dye because of the low levels of dye-fiber fixation [35]. Discharge of these pharmaceuticals into effluents affects the people who may use these effluents for living purposes such as washing, bathing and drinking [36]. Therefore It is very important to verify the water quality, especially when even just 1.0mg/L of dye concentration in drinking water could impart a significant color, making it unfit for human consumption [37]. Furthermore

pharmaceuticals can affect aquatic plants because they reduce sunlight transmission through water. Also pharmaceuticals may impart toxicity to aquatic life and may be mutagenic, carcinogenic and may cause severe damage to human beings, such as dysfunction of the kidneys, reproductive system, liver, brain and central nervous system [38–40]. The removal of color from waste effluents becomes environmentally important because even a small quantity of dye in water can be toxic and highly visible [41]. Since the removal of pharmaceuticals from wastewater is considered an environmental challenge and government legislation requires textile wastewater to be treated, therefore the reisa constant need to have an effective process that can efficiently remove these pharmaceuticals [42].

In view of the aforesaid problems, recently much attention has been focused on the development of more effective, lower-cost, robust methods for waste-water treatment, without further stressing the environment or endangering human health by the treatment itself [43]. Extensive studies have been undertaken in recent years with the aim of finding alternative and economically feasible technologies for water and waste-water treatment. Discharge of dyeing industry waste-water into natural water bodies is not desirable as the colour prevents reoxygenation in receiving water by cutting off penetration of sunlight. This upsets the biological activities in water bodies. Most of the pharmaceuticals used as colouring materials are toxic to aquatic organisms [44]. In addition, wastewaters from dyeing and textile industries easily produce toxic tri halo methanes when chlorinated [45]. Methods such as chemical coagulation [46], ozonization [47], membrane filtration [48], electrolysis [49], oxidation [50] and bio-degradation have been widely used for the removal of pharmaceuticals from water and wastewater. Adsorption has become one of the most effective and comparatively low cost methods for the decolorization of textile waste-water [51-53]. Numerous approaches have been made by various researchers to develop cheaper and effective adsorbents to remove pharmaceuticals from a variety of starting materials from waste [54]. Adsorption is by far the most effective and non-destructive technique that is widely used for the removal of pharmaceuticals from aqueous solutions. It is attractive as the adsorbed pharmaceuticals can be recovered with suitable regenerating agents. To make the treatment process economic, several investigators have concentrated their work on low cost, adsorbent materials. Textile industries have shown a significant increase in the use of synthetic complex organic pharmaceuticals as colouring materials [55]. Adsorption has been found to be more efficient to other techniques for water treatment in terms of simplicity of design, initial cost, use of operation and insensitivity to toxic substances [56]. Adsorption has been used extensively in industrial process for separation and purification. The removal of coloured and colourless organic pollutants from industrial wastewater is considered as an important application of adsorption processes [57]. The major advantages of an adsorption treatment for the control of water pollution are less investment in terms of initial development cost, simple design, easy operations, free from generation of toxic substances and easy and safe recovery of the adsorbent as well as adsorbate materials [58]. In the adsorption

technique the major concern is the selection of adsorbent material. In recent years “adsorption” process became more popular as “biosorption” by the application of biomaterials as adsorbent for contaminated water treatment [59]. However this process has not widely employed in industrial scale for waste-water treatment. Also the application of magnetic adsorbent technology for separation of pollutants in water has received considerable attention in recent years. During the past decade, great efforts have been devoted to the preparation of variety of magnetic composites/materials for waste-water treatment. Magnetic adsorbents are an attractive solution for metallic and dye pollutants, particularly due to the simple magnetic separation process.

There are many structural varieties of pharmaceuticals that fall into either the cationic, nonionic or anionic type. Anionic pharmaceuticals are the direct, acid and reactive pharmaceuticals [60]. Brightly coloured, Water soluble reactive and acid pharmaceuticals are the most problematic, as they tend to pass through conventional treatment systems unaffected [61]. Municipal aerobic treatment systems, dependent on biological activity, were found to be incient in the removal of these pharmaceuticals [62]. Nonionic pharmaceuticals refer to disperse pharmaceuticals because they do not ionise in an aqueous medium. Concern arises, as many pharmaceuticals are made from known carcinogens such as benzidine and other aromatic compounds [63, 64] demonstrated that azo- and nitro-compounds are reduced in sediments, and similarly Chung et al. [65] illustrated their reduction in the intestinal environment, resulting in the formation of toxic amines. Anthroquinone-based pharmaceuticals are most resistant to degradation due to their fused aromatic ring structure. The ability of some disperse pharmaceuticals to bio accumulate has also been demonstrate. [66]. This review illustrates the critical study of the most widely used methods of dye removal from dye-containing industrial effluents. These methods have been discussed under three categories: chemical, physical and biological. Currently the main methods of textile dye treatment are by physical and chemical means (Table 1) with research concentrating on cheaper effective alternatives.

Adsorption methods employing solids adsorbents are widely used to remove certain classes of chemical pollutants from wastewater. However, among all the sorbent materials proposed, activated carbon (AC) is the most popular material for the removal of pollutants from wastewater. AC is an amorphous carbon compound in which a high degree of porosity has been developed during manufacture. It is this porosity, which governs the way in which AC performs its purifying role, and the very large surface area provides many sites upon which the adsorption of impurity molecules can take place. The factors which favor the selection of agricultural adsorbents are its low-cost, widespread presence and organic composition which shows strong affinity for some selected pharmaceuticals. Because be disposed of without expensive regeneration. A wide variety of ACs has been prepared from agricultural byproducts.

Advantages and disadvantages of the current methods of dye removal from industrial effluents		
Physical/chemical methods	Advantages	Disadvantages
Activated carbon	Good removal of wide variety of pharmaceuticals	High cost
Cucurbituril	Good sorption capacity for various pharmaceuticals	Very expensive
Electro kinetic coagulation	Economically feasible	High sludge production
Irradiation	Effective oxidation at lab scale	Requires a lot of dissolved O ₂
NaOCl	Initiates and accelerates azo-bond cleavage	Release of aromatic amines
Ozonation	Applied in gaseous state: no alteration of volume	Short half-life (15-20 min)
Membrane filtration	Removes all dye types	Sludge production
Peat	Good adsorbent due to cellular structure	Specific surface areas for adsorption are lower than activated carbon

Pharmaceuticals	Adsorbents	Equilibrium time	q _e (mg/g)	References
Malachite green	Neem bark	7 h	0.36	67
Malachite green	Mango bark	7 h	0.53	68
Malachite green	Pandanus leaves	40 min	9.737	69
Congo red	Tamarind shell	4h	10.48	70
Acid blue	Pitch pine saw dust	60 min	27.5	71
Methylene blue	Cherry saw dust	2 h	39	71
Rhodamine B	Banana bark	40 min	40.161	72
Methylene blue	Sunflower seed husk	4 h	45.25	73
Malachite green	Rice husk	40 min	63.85	74
Congo red	Neem leaf powder	5 h	72	75
Methylene blue	Hazlenut shell	60 min	76.9	71
Methylene blue	Rice husk	30 min	690	76
Malachite green	Neem bark	7 h	0.36	67
Malachite green	Mango bark	7 h	0.53	68
Malachite green	Pandanus leaves	40 min	9.737	69

The main aim of the review of the past work is to give an idea for the systematic study of the utilization of low cost adsorbents for the removal of pharmaceuticals from aqueous solution and from industrial effluents. Among various ways of treating industries effluents containing pharmaceuticals, one can utilize the resources of inexpensive techniques.

The summary of the published data with some of the latest important results with up to date literatures on the adsorption properties of some alternatives adsorbents used for the removal of the pharmaceuticals. Photo catalytic and adsorption studies on the removal of dye Congo red from wastewater investigated by Rajeev Jain and Shalini Sikarwar [77] The photocatalytic results of the study indicate that anatase titanium dioxide, as a catalyst is very efficient and effective to enhance the photocatalytic activity. Catalyst concentration and additives such as H_2O_2 were used to obtain a high degradation rate of Congo red. Removal of Colour from Different Dye Wastewater by Using Ferric Oxide as an Adsorbent was reported by Kartik H. Gonawala & Mehali J. Mehta [78]. They are concluded that Fe_2O_3 powder is used for removal of Color from textile dye wastewater by batch experiments. Adsorption Equilibrium is attained within 45 min. It obeyed Freundlich isotherm model as compared to Langmuir isotherm and Tempkin isotherm. The order of disperse blue 73 (Anthraquinone dye) adsorption was governed by pseudosecond-order kinetics. Removal of Pharmaceuticals from Wastewater Using Bottom Ash studied by V. K. Gupta. et. al [79] and they represent the bottom ash generated in a MSWI was used as a low-cost adsorbent for the removal of alizarin yellow, fast green, and methyl violet from wastewater. The adsorption of alizarin yellow and fast green has been found to be exothermic, whereas it is endothermic in the case of methyl violet. The results indicate that both the Freundlich and Langmuir models can be used to fit the data and estimate the model parameters.

Degradation of Congo Red Solution by Zinc Oxide/Silver Composite Preheated at Different Temperatures article reported by Oda. et al [80]. Congo red dye was degraded with high photo degradation efficiency by sun light. The reaction done without focusing sun radiant and the catalyst work properly. The photo oxidation of methanol in the photo deposition making Ag ion converts to Ag_2O system making a good doping on the ZnO surface.

Chaudhary. et al investigated the use of chromium waste sludge for the adsorption of colour from dye effluent streams [81]. Adsorption studies reveals that chromium hydroxide precipitates can be used as an adsorbent for the removal of Methylene blue, Reactive blue, Congo red and disperse Orange pharmaceuticals from aqueous system. It include three different mechanisms such as; attraction of negative surface charges on hydroxide at high pH for dye cations (Methylene blue), attraction of positive surface charges on the precipitate at low pH for dye anions (Reactive blue and Congo red) and dye particle entrapment for the neutral disperse orange.

III. CONCLUSION

The presence of pharmaceuticals in industrial effluents when exceed the permissible limit causes various disorders such as allergic dermatitis, skin irritation, cancer etc. the prominent effect of their presence is the visual coloration of the water. Adsorption process is the most widely used and effective method. This technique offers much potential in the treatment of dye-containing effluents. It has been concluded that removal of pharmaceuticals with adsorption technique using low cost/no cost adsorbent materials like naturally occurring, agricultural and industrial waste materials, has been found to be more effective with better removal efficiency. By utilizing waste discharged residues as adsorbents thereby, would improve textile industry economically.

REFERENCES

1. Kim S, C. Park, T.H. Kim, J. Lee and S.W. Kim., COD reduction and decolorisation of textile effluents using a combined proc Hillenbrand T, Bohm E, Landwehr M, Marscheider-Weidemann F. Die Abwassersituation in der de (The wautschen Papier, Textil-und Lederindustric textile, and tannery industry), Gwf Wasser Abwasser;140:267-73, 1999.
2. Hillenbrand T, Bohm E, Landwehr M, Marscheider-Weidemann F., Die Abwassersituation in der de(The wautschen Papier, Textil-und Lederindustric textile, and tannery industry), Gwf Wasser Abwasser;140:267-73, 1999.
3. Kalliala E, Talvenmaa P., Environmental profile of textile wet processing in Filand, *J Cleaner Prod*; 8:143-54, 2000.
4. Cooper P. (Ed.), Color in Dyehouse Effluent, The Society of Dyers and Colorists, Alden Press, Oxford, 1995.
5. Gupta V.K., Mittal A, Gajbe V., Adsorption and desorption studies of a water soluble dye, Quilnoline Yellow, using waste materials, *J. Colloid Interf. Sci*, 284, 89-98, 2005.
6. Mohan S.V, Roa C.N, Prasad K.K., Karthikeyan J., Treatment of simulated reactive yellow 22 (Azo) dye effluents using Spirogyra species, *Waste Manage*, 22, 575-58, 2002.
7. Gupta V.K., Suhas I.A., Mohan D., Equilibrium uptake and sorption dynamics for the removal of a basic dye (basic red) using lowcost adsorbents, *J. Colloid Interf. Sci*, 265, 257-264, 2003.
8. Kumar K.V, Ramamurthi V, Sivanesan S., Pharmaceuticals and pigments, biosorption of Malachite, a green cationic dye onto Pithophora sp., a fresh water algae, *Pharmaceuticals Pigments*, 69, 74-79, 2006.
9. Henderson A L, Schmitt T C, Heinze T M and Cerniglia C E., Reduction of malachite green to leucomalachite green by intestinal bacteria, *Appl Environ Microbiol*, 63,4099-4101, 1997.
10. Lambert S D., Evaluation of inorganic adsorbents for the removal of problematic textile pharmaceuticals and pesticides, *Water Technol.*, 36, 173-180, 1997.

11. Keharia H, Madamvar D., Bioremediation concept for treatment of dye containing wastewater: a review, *Indian J. Exp. Biol.* 41, 1068–1075, 2003.
12. Reife A., Pharmaceuticals, environmental chemistry, In: Kirk-Othmer encyclopedia of chemical technology, 4th Ed. Washington: John Wiley and Sons, 753, 1993.
13. Shannon MA, Bohn PW, Elimelech M, Georgiadis JG, Marinas BJ, et al., Science and technology for water purification in the coming decades, *Nature*, 452:310-310, 2008.
14. Chong MN, Jin B, Chow CWK, Saint C., Recent developments in photocatalytic water treatment technology: A review, *Water Res*, 44:2997-3027, 2010.
15. Ruthven DM., *Principles of Adsorption, Desorption Processes*, Wiley, New York, 1984.
16. Suzuki M (Ed.), *Fundamentals of Adsorption IV*, Kodansha, Tokyo, 1993.
17. G. McKay, M.S. Otterburn, D.A. Aga., Fullers earth and fired clay as adsorbent for dye stuffs, equilibrium and rate constants, *Water Air Soil Pollut.* 24: 307–322, 1985.
18. A.R. Gregory, S. Elliot, Kluge. P., Ames testing of direct black 3B parallel carcinogenicity, *J. Appl. Toxicol.* 1: 308–313, 1993.
19. Gercel O, Gercel H. F., Koparal A. S. and Oğutveren. U.B., Removal of disperse dye from aqueous solution by novel adsorbent prepared from biomass plant material, *Journal of Hazardous Materials*, 160: 668-674, 2008.
20. Karaca S, Gurses A, Acıkyıldız M. and Ejder (Korucu). M., Adsorption of cationic dye from aqueous solutions by activated carbon, *Microporous and Mesoporous Materials*, 115:376-382, 2008.
21. Reddy DHK, Ramana DKV, Sessaieh K, Reddy AVR., Biosorption of Ni(ii) from aqueous phase by *Moringa oleifera* bark, a low cost biosorbent. *Desalination*, 268:150-157, 2011.
22. Ramakrishna KR, Viraraghavan T., Dye removal using low cost adsorbent, *Water Sci. Technol.* 36:189, 1997.
23. Khanna SK, Das M., Toxicity, carcinogenic potential and clinicoepidemiological studies on pharmaceuticals and dye intermediates. *J Sci Ind Res* ;50:965–74, 1991.
24. McKay G., Waste color removal from textile effluents. *Am Pharmaceuticalstuff Rep* ;68:29–34, 1979.
25. Ruthven DM., *Principles of Adsorption Desorption Processes*. Wiley, New York, 1984.
26. Suzuki M (Ed.), *Fundamentals of Adsorption*. edition IV , Kodansha, Tokyo, 1993.
27. Bailey SE, Plin TJ, Bricka RM, Adrain DD., A review of potentially low cost sorbents for heavy metals. *Wat. Res.* 3 :2469-2479, 1999.
28. Gupta VK, Ali A., Adsorbents for water treatment: low-cost alternatives to carbon. In: H. Arthur, (Ed.), *Encyclopedia of Surface and Colloid Science*. Marcel Dekker, USA, 1: 136-166, 2002.
29. Zhou M, He J., Degradation of azo dye by three clean advanced oxidation processes: Wet oxidation, electrochemical oxidation and weelectrochemical oxidation-A comparative study, *Electrochimica Acta* ,53: 1902-1910, 2007.
30. Pruden AL, Ollis DF., Photoassisted heterogeneous catalysis: the degradation of trichloroethylene in water *J.Catal.*82: 404-417, 1983.
31. Jain R, Mittal A, Mathur M, Sikarwar S., Removal of the hazardous dye Rhodamine B from photocatalytic and adsorption treatments, *J. Environ. Manage*, 85:956-960, 2007a.
32. Jain R, Varshney S, Sikarwar S., Electrochemical techniques for the removal of Reactofix Golden yellow 3 RFN from industrial wastes , *J. Coll. Interf. Sci.* 313: 248-253, 2007b.
33. Gupta VK, Ali A., Adsorbents for water treatment: low-cost alternatives to carbon. In: H. Arthur, (Ed.), *Encyclopaedia of Surface and Colloid Science*, Marcel Dekker, USA. 1:136-166, 2002.
34. N.Mohan, N.Balasubramanian, C.A.Basha., Electrochemical oxidation of textile wastewater and its reuse, *J.Hazard.Mater.* 147: 644–651. [2] M.K., 2007.
35. Sharma, R.C.Sobti., Recept of certain textile pharmaceuticals in *Bacillus subtilis*, *Mutat. Res.Genet.Toxicol.Environ. Mutagen.* 465: 27–38. [3] R, 2000.
36. Malik, D.S.Ramteke ,S.R.Wate., Adsorption of malachite green on groundnut shell waste based powdered activated carbon, *WasteManag.* 27: 1129–1138, 2007.
37. Kadirvelu, M.Kavipriya, C.Karthika, M.Radhika, N.Venilamani, S.Pattabhi., Utilization of various agricultural wastes for activated carbon preparation and application for the removal of pharmaceuticals and metal ions from aqueous solutions, *J. Biores. Technol.* 87: 129–132, 2003.
38. A.R.Dinçer, Y.Günes, N.Karakaya, E.Günes., Comparison of activated carbon and bottomash for removal of reactive dye from aqueous solution, *J.Biores. Technol.* 98:834–839, 2007.
39. D. Shen, J.Fan, W.Zhou, B.Gao, Q.Yue, Q.Kang., Adsorption kinetics and iso-therm of anionic pharmaceuticals onto organo-bentonite from single and multisolute systems, *J. Hazard. Mater.* 172: 99–107, 2009.
40. Y.Li., Adsorption of anionic pharmaceuticals in acid solutions using chemically cross-linked chitosan beads, *J. Pharmaceuticals Pigm.* 6069–84, 2004.
41. P. Choi, R. Thiruvengkatahari, W.-G. Shim, H. Moon. 2004. Evaluation of the performance of adsorption and coagulation processes for the maximum removal of reactive pharmaceuticals, *J. Pharmaceuticals Pigm.* 69:196–203, 2004.
42. Chagas EP, Durrant LR., Decolourization of azo pharmaceuticals by *Phanerochaete chrysosporium*, *Enzyme Microb. Technol*, 29:473, 2001.
43. Malik PK., Use of activated carbon prepared from sawdust and rice husk for adsorption of acid pharmaceuticals: a case study of acid yellow 36, *Pharmaceuticals Pigments.* 56:23, 2003.
44. Nigam P, Armour G, Banat I, Singh MD, Merchant R., Physical removal of textile pharmaceuticals from effluents and solid-state fermentation of dye-adsorbed agriculture residues, *Bioresour. Technol*, 72:219, 2000.

45. Seshdari S, Bishop PL, Agha AM., Anaerobic-aerobic treatment of selected azo pharmaceuticals in wastewater, *Waste Manag.* 15:127, 1994.
46. Namasivayam C, Radhika R, Suba S., Uptake of pharmaceuticals by a promising locally available agricultural solid waste: coir pith, *Waste Manage.* 21:381, 2000.
47. McKay G, Allen SJ, Meconney IF, Ottrburn MS., Transport processes in the sorption of coloured ions by peat particles, *J. Colloid. Interface Sci.* 80(2):323, 1981.
48. Grag, V.K. Raksh Kumar and Renuka Gupta., Removal of malachite green dye from aqueous solution by adsorption using agroindustries waste: A case study of *Phosopis cineraria*, *Pharmaceuticals & Pigments*, 62: 1-10, 2004.
49. Gang RM, Li M, Yang C, Sun YZ, Chen J., Removal of cationic pharmaceuticals from aqueous solution by adsorption onto peanut hull. *J. Hazard. Mater.*, 121: 247-250, 2005.
50. Gupta VK, Carrott PJM, Ribeiro C, Suhas MML., Low cost adsorbents: Growing approach to wastewater treatment –A review, *Critical Reviews in Environmental Sci. Technol.* 39: 783–842, 2009.
51. Annadurai G, Juang R.S, and Lee D.J., Use of cellulose-based waste for adsorption of pharmaceuticals from aqueous solutions, *Journal of Hazardous Materials* B92:263-274, 2002.
52. Arami M, Limaee N.Y, Mahmodi N.M., Investigation on the adsorption capability of egg shell membrane towards model textile pharmaceuticals, *Chemosphere* 65: 1999-2008, 2006.
53. Ozer D, Dursun G. and Ozer A., Methylene blue adsorption from aqueous solution by dehydrated peanut hull, *Journal of Hazardous Materials*, 144:171-179, 2007.
54. Hameed B.H., Din A.T.M., and Ahmad A.L., Adsorption of methylene blue onto bamboo-based activated carbon: Kinetics and equilibrium studies, *Journal of Hazardous Materials*, 141: 819-825, 2007.
55. Talarposhti A.M., Donnelly T., Anderson G.K., Colour removal from a simulated dye wastewater using a two-phase anaerobic packed bed reactor, *Water Research*, 35(2): 425, 2001.
56. Meshko V., Markovska L., Minchev M., Rodrigues A.E., Adsorption of basic pharmaceuticals on granular activated carbon and natural zeolite, *Water Research*, 35(14): 3357, 2001.
57. Al-Qodah Z., Adsorption of pharmaceuticals using shale oil ash, *Water Research*, 34(17): 4295, 2000.
58. G. Crini., Non-conventional low-cost adsorbents for dye removal: A review, *Bioresour. Technol.*, 97:1061–1085, 2006.
59. Vadivelan V, Kumar KV., Equilibrium, kinetics, mechanism and process design for the sorption methylene blue onto rice husk, *J. Colloid Interf. Sci.*, 286: 90-100, 2005.
60. Mishra, G., Tripathy, M., A critical review of the treatments for decolourization of textile e.uent. *Colourage* 40: 35±38, 1993.
61. Willmott, N., Guthrie, J., Nelson, G., The biotechnology approach to colour removal from textile e.uent. *JSDC* 114:38±41, 1998.
62. Moran, C., Hall, M.E., Howell, R.C., Effects of sewage treatment on textile e.uent. *J. Soc. Dyers. Colour.* 113:272±274, 1997.
63. Baughman, G.L., Perenich, T.A., Fate of pharmaceuticals in aquatic systems: I Solubility and partitioning of some hydrophobic pharmaceuticals and related compounds. *Environ. Toxicol. Chem.* 7:183±199, 1988.
64. Weber, E., Wolfe, N.L., Kinetics studies of reduction of aromatic azo compounds in anaerobic sediment/water systems. *Environ. Toxicol. Chem.* 6: 911±920, 1987.
65. Chung, K.T., Fulk, G.E., Egan, M., Reduction of azo pharmaceuticals by intestinal anaerobes. *Appl. Environ. Microbiol.* 35: 558±562, 1978.
66. Baughman, G.L., Perenich, T.A., Fate of pharmaceuticals in aquatic systems: I Solubility and partitioning of some hydrophobic pharmaceuticals and related compounds. *Environ. Toxicol. Chem.* 7: 183±199, 1988.
67. S. Arivoli, M. Thenkukuzhali, P. Martin Deva Prasath., Adsorption of rhodamine B by acid activated carbon : kinetic, thermo dynamic and equilibrium studies, *Electron. J. Chem.* 1(2): 138–15, 2009.
68. R. Srivastava, D. C. Rupainwar., A comparative evaluation for adsorption of dye on neem bark and mango bark powder, *Indian J. Chem. Technol.* 18: 67–75, 2011.
69. M. Hema, S. Arivoli., Adsorption kinetic and thermo dynamics of malachite green dye into acid activated low cost carbon, *J. App. Sci. Environ. Manag.* 12 (1): 43–51, 2008.
70. M.C. Somasekhara Reddy., Removal of direct dye from aqueous solution with an adsorbent made from tamarind fruits hell, an agricultural solid waste, *J. Sci. Ind. Res.* 65: 443–446, 2006.
71. Ferrero., Dye removal by low cost adsorbents : hazelnutshellin comparison with wood saw dust, *J. Hazard. Mater.* 142 144–152, 2007.
72. S. Arivoli, M. Thenkukuzhali, P. Martin Deva Prasath., Adsorption of rhodamine B by acid activated carbon : kinetic, thermodynamic and equilibrium studies, *Electron. J. Chem.* 1(2): 138–15, 2009.
73. S.T. Ong, P.S. Keng, S. L. Lee, M.H. Leong, Y.T. Hung., Equilibrium studies for the removal of basic dye by sunflower seedhusk (*Helianthus annuus*), *Int. J. Phys. Sci.* 5(8): 1270–1276, 2010.
74. Y. C. Sharma, B. Singh, Uma., Fast removal of malachite green by adsorption on rice husk activated carbon, *Open Environ. Pollut. Toxicol. J.* 1: 74–78, 2009.
75. K.G. Bhattacharyya, A. Sharma., Azadirachtaindica leaf powder as an effective biosorbent for pharmaceuticals : a case study with aqueous Congo Red solutions, *J. Environ. Manag.* 71: 217–229, 2004.
76. S. Chandrasekhar, P.N. Pramada., Rice husk as a shasanad – sorbent for methylene blue—effect of ashing temperature, *Adsorption* 12: 27–43, 2006.

77. Jain, R. and Sikarwar, S., Photocatalytic and adsorption studies on the removal of dye Congo red from waste water ,*Int. J. Environment and Pollution*, Vol. 27, Nos. 1/2/3:158–178, 2006.
78. Kartik H. Gonawala et al *Int., Journal of Engineering Research and Applications* ISSN : 2248-9622, Vol. 4, Issue 5, Version 6:102-109, 2014.
79. V. K. Gupta, Imran Ali, V. K. Saini, Tom Van Gerven, Bart Van der Bruggen, and Carlo Vandecasteele Ind., Removal of pharmaceuticals from wastewater using bottom ash *Eng. Chem.* 44:3655-3664, 2005.
80. Amjed Mirza Oda, Salih Hadi Kadhum, Ahmed Salih Farhood and Hussain Abdul alkadhum., Degradation of Congo Red Solution by Zinc Oxide/Silver Composite Preheated at Different Temperatures *Thermodynamics and catalysis, j thermo dynamcat* vol 5:127, 2005.
81. y, Bijita Ganguli, Susan M Grimes., The use of chromium waste sludge for the adsorption of colour from dye effluent streams, *Journal of Chemical Technology & Biotechnology: International Research in Process, Environmental & Clean Technology* 77 (7):767-770, 2002.