

Analysis of Different Type Of Materials, Stainless Steel & Aluminium Using For Steam Generation

NITESH RANE¹, JITENDRA PATIDAR²

^{1,2}Department of Mechanical Engineering, Dr. A. P. J. Abdul Kalam University, Indore
Corresponding Author Email: nrane1991@gmail.com

Abstract— The growth of the modern society has been fueled by cheap, abundant energy resources. Solar energy is a form of renewable energy which is available abundantly and collected unreservedly. In the application of solar energy using parabolic trough is analyzed. Parabolic trough technology is currently the most extended solar system for electricity production or steam generation for industrial processes. It is basically composed of a collector field which converts solar irradiation into thermal energy and a conventional thermal to electric conversion Rankine Cycle. The prototype of the parabolic trough concentrating solar is collector manufactured using the available materials and equipment in the workshop of Mechanical Engineering Department. The prototype is designed using Pro-Engineering software. An experimental setup has been developed to investigate the performance of the parabolic trough. Measurements of total direct radiation on the plane of the collector, ambient temperature, wind speed, water flow rate, and inlet and outlet temperatures of the water inside the absorber tube are collected and employed in studying the performance of the parabolic trough. The material used is stainless steel sheet as a reflector and plywood material as a sub frame; The Different type of pipe use for water circulation that is stainless steel pipe, Aluminum pipe that is covered with glass tube and also comparers which of the efficiency High in all the materials use in this.

Index Terms— Solar parabolic trough, Stainless steel pipe, Aluminium pipe, electronic circuit (Depend on the H-bridge & Wheat-stone bridge concept).

I. INTRODUCTION

In present, energy is primary demand for human culture. The country within which a lot of energy produce is a lot of developed than alternative. Energy is incredibly necessary for doing any work. All the energy sources we have a tendency to square measure victimization nowadays is classified into 2 groups; renewable and non-renewable. Renewable energy comes by natural processes which are resupply constantly. In its numerous forms, it derives directly from the sun.

Energy generated from solar, wind, ocean, tidal, hydropower, biomass, energy resources, bio fuels and hydrogen is renewable resources. Non-renewable energy is energy sources that can't resupply within the close to future like coal, oil, oil and gas. Renewable and non-renewable energy sources are accustomed produce secondary energy sources as electricity related to human activities became more and more serious.

Additionally to a rise in value of fuel product and resources are going to be exhausted in an exceedingly comparatively

short amount of your time. This high cost of fuel resources square measure poignant economic and social development worldwide. The impact of energy crises is especially felt in less developed countries where a high percentage of national budgets for development should be pleased to the purchase of fuel product. to reduce the dependency on foreign fuels with high worth, most countries have initiated programs to develop energy sources supported domestic renewable resources.

In order to attain the goals of property development, it's essential to attenuate the consumption of finite natural resources and to mitigate the environmental burden to among nature's restorative capability.

There is currently a global accord that the new sources of energy need to be renewable to satisfy the global energy demand within the long run. Solar thermal power plants square measure one among the foremost promising choices for renewable electric power production not like traditional power plants, concentrating solar energy systems offer an environmentally friendly supply of energy, produce nearly no emissions, and consume no fuel other than sunlight. The goal of this project is to identify general strategies and specific design ideas for achieving increased collector efficiency. This thesis has investigated enhancements within the design of a parabolic trough module by wanting 1st at the structural conception of the collector to scale back quality whereas maintaining structural stability. The water is applied because the heat transfers fluid in an exceedingly solar parabolic trough collector system. Firstly, the system dynamic model was established and valid by the important in operation

Energy is one among the crucial inputs for socio-economic development the rate at which energy is being consumed by a nation typically reflects the amount of prosperity that it might come through and total energy consumption has enhanced along with economic and population growth and, at a similar time, varied environmental issues information in typical summer and spring days in references. Secondly, the alteration characteristics of much radiation, recess water temperature and rate of flow are analyzed and compared with the standard operating condition.

II. DESIGN OBJECTIVES

The general objective of this research is to design, manufacture and by experimentation investigate the performance of the model parabolic trough solar energy generation system. The experimental investigation determines the temperature variations of the current fluid, the solar

energy absorption rate, the temperature variations of the ambient temperature and therefore the instant efficiency of the system as a perform of time.

The specific objectives of the project are:-

III. METHODOLOGY

- Design and modelling of Parabolic Trough Manufacturing the system.
- Experimental investigation of the system considering totally different parameters.
- Manufacturing prototype: After the design process is completed, the prototype is manufactured. Based on the design parameters and design materials, the prototype of the parabolic trough is manufactured in the Mechanical Engineering Department workshop.
- Installation of Prototype: The prototype of the parabolic trough is installed at the site very close to the Mechanical Engineering Department.
- Experimental Investigation: After the prototype is installed, experimental investigation were conducted by recording data.
- Analysis and Interpreting the Result: The test results are compiled and compared with the results obtained using a mathematical model to check the validity of the result & compare all the result.

IV. MODELLING OF THE SYSTEM

The Parabolic concentrating collector assembly was modelled by using CRE-O





Figure1. Assembly

Component	Dimension
Diameter of tube	25 cm
Width	80 cm
Focal Length	30 cm
Length	320 cm

Individual components were designed in 3 D and then were assembled.

V. COMPARISON BETWEEN STAINLESS STEEL PIPE & ALUMINIUM PIPE, WITH GLASS COVER TUBE TEST RESULT WITH THE HELP OF GRAPH



The efficiency of the parabolic trough where use absorber of stainless steel highest efficiency 85.29%. This is efficiency for Stainless steel absorber pipe use its improvement is also expected from parabolic troughs covered with glass or transparent material. This increases the efficiency of the parabolic trough by reducing convection heat loss from the absorber tube and prevents the reflector from dust particle. On the same setup we use different material aluminum there we getting highest efficiency 80.71% also covered with glass or transparent material for increases the efficiency of the parabolic trough. Compare to both the materials use in absorber pipe we get the highest efficiency in the stainless steel pipe 85.29%.

VI. CONCLUSION

In this experiment we are use different type of material in absorber pipe all the absorbers gives the different efficiency compare to stainless steel in this observation, we use different material like iron, mild steel, aluminum and getting the different efficiency.

The efficiency of the parabolic trough where use absorber of stainless steel highest efficiency 85%. This is efficiency for Stainless steel absorber pipe use its improvement is also expected from parabolic troughs covered with glass or transparent material. This increases the efficiency of the parabolic trough by reducing convection heat loss from the absorber tube and prevents the reflector from dust particle.

On the same setup we use different material aluminum there we getting highest efficiency 80.71% also covered with glass or transparent material for increases the efficiency of the parabolic trough.

REFERENCES

1. Garud S. Making solar thermal power generation in India reality overview of technologies, opportunities and challenges, the energy and resources institute (TERI) India, http://www.aprek.org/files/SolarThermalPowergeneration_Final.pdf.
2. Laing, D., Steinmann W.D., Tamme R. and Richter C. examination of Solid media thermal storage for parabolic trough power plants. Vol- 80, page 1283–1289, Germany, 2006.

3. Qu.M., Archer D.H. and Masson S.V. A linear Parabolic Trough Solar Collector Performance Model. Renewable Energy Resources and a Greener Future, Vol.VIII-3-3, USA, 2006.
4. Arancibia-Bulnes C.A., and Cuevas S.A. Modeling of the radiation field in a parabolic trough solar photocatalytic reactor. Mexico, 2004.
5. E. Zarza, L. Valenzuela, J. Leon, K. Hennecke, M. Eck, H.D. Weyers, & M. Eickhoff, "Direct Steam Generation in Parabolic Troughs: Final Results and Conclusions of the DISS Project," *Energy*, vol. 29, pp. 635-644, 2004.
6. Y. Shuai, X. Xia, H. Tan, "Radiation performance of dish solar concentrator cavity receiver systems," *Solar Energy*, vol. 82, Issue 1, pp.13-21, 2008.
7. C.A. Estrada, O.A. Jaramillo, R. Acosta, C. Arancibia-Bulnes, "A Heat transfer analysis in a calorimeter for concentrated solar radiation measurements," *Solar Energy*, vol. 81, Issue 10, pp. 1306-1313, 2007.
8. A Primer on CPV Technology, SolFocus, available online at <<http://www.solfocus.com/>>, (accessed May 2008)
9. Bakos, G. C., Adamopoulos, D., Soursos, M. and Tsagas, N. F. Design and construction of a line-focus parabolic trough solar concentrator for electricity generation, 1999.